

Contents lists available at [ScienceDirect](#)

# Engineering

journal homepage: [www.elsevier.com/locate/eng](http://www.elsevier.com/locate/eng)

## Corrigendum

### Corrigendum to “Dual-Comb Ranging” [Engineering 4 (2018) 772–778]

Zebin Zhu <sup>a</sup>, Guanhao Wu <sup>a,b,\*</sup><sup>a</sup>State Key Laboratory of Precision Measurement Technology and Instruments, Department of Precision Instrument, Tsinghua University, Beijing 100084, China<sup>b</sup>Division of Advanced Manufacturing, Graduate School at Shenzhen, Tsinghua University, Shenzhen 518055, China

The authors regret to inform that important information was missing in Eq. (14). The corrected Eq. (14) appears below:

$$\delta\varphi_r(t) = 2\pi \int_0^t \delta f_r(\tau) d\tau \quad (14)$$

DOI of original article: <https://doi.org/10.1016/j.eng.2018.10.002>

\* Corresponding author.

E-mail address: [guanhaowu@mail.tsinghua.edu.cn](mailto:guanhaowu@mail.tsinghua.edu.cn) (G. Wu).

<https://doi.org/10.1016/j.eng.2019.01.005>

2095-8099/© 2019 THE AUTHORS. Published by Elsevier LTD on behalf of Chinese Academy of Engineering and Higher Education Press Limited Company. This is an open access article under the CC BY license (<http://creativecommons.org/licenses/by/4.0/>).